



### FH254-XXX-XXX

Female Header  
Pitch 2.54mm  
4: Four Row  
3: Three Row  
2: Dual Row  
1: Single Row

Type1/Type2  
.....  
No.of Pins  
Four Row: 4~40  
Three Row: 3~40  
Dual Row: 2~40  
Single Row: 2~40

#### PRODUCT SPECIFICATION

- INSULATOR MATERIAL : POLYESTER, UL94V-0.
- TERMINAL MATERIAL : COPPER ALLOY.
- FINISH : GOLD OR TIN PLATED.
- CURRENT RATING : 3 AMPERE.
- INSULATION RESISTANCE : 1000M OHMS MIN.
- DIELECTRIC WITHSTANDING VOLTAGE : 1000 V /1 MINUTE.
- CONTACT RESISTANCE : 初期 Initial : 20 m Ohm Max. ;  
测试后 Final : 40 m Ohm Max..
- OPERATING TEMPERATURE : - 40°C to +105°C.

DIM A	DIM B
5.70	3.00
8.00	3.00
8.50	3.00/3.20
11.0	3.00

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 08012016	东莞市宇亮电子有限公司 DONG GUAN YU LIANG ELECTRONICS CO.,LTD	
		CHEK 08Jan2016		
		APVD Abel 08Jan2016	NAME Female Header 2.54mm DIP Type	
		PRODUCT SPEC	DRAWING No. YL-ED-XXX	
		WEIGHT	SIZE A4	SCALE 1 : 1
		CUSTOMER DRAWING	SHEET 1 of 1	