



PH200-XXX-XXX

Female Header
Pitch 2.00mm
4: Four Row
3: Three Row
2: Dual Row
1: Single Row

Type1/Type2
.....
No. of Pins
Four Row: 4~40
Three Row: 3~40
Dual Row: 2~40
Single Row: 2~40

PRODUCT SPECIFICATION

1. INSULATOR MATERIAL : POLYESTER, UL94V-0 .
2. TERMINAL MATERIAL : COPPER ALLOY .
3. FINISH : GOLD OR TIN PLATED.
4. CURRENT RATING : 2 AMPERE.
5. INSULATION RESISTANCE : 1000M OHMS MIN.
6. DIELECTRIC WITHSTANDING VOLTAGE : 1000 V /1 MINUTE.
7. CONTACT RESISTANCE : 初期 Initial : 20 m Ohm Max. ;
测试后 Final : 40 m Ohm Max. .
8. OPERATING TEMPERATURE : - 40°C to +105°C.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	0801092016	
<p>THIRD ANGLE PROJECTION</p>	TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHEK	08Jan2016
	0 PLC	± 0.50	APVD	Abel 08Jan2016
	1 PLC	± 0.30	PRODUCT SPEC	—
	2 PLC	± 0.20	WEIGHT	—
3 PLC	± 0.15	CUSTOMER DRAWING		
4 PLC	± —			
ANGLES	± 3°			

东莞市宇亮电子有限公司 DONG GUAN YU LIANG ELECTRONICS CO.,LTD	
NAME	
Female Header 2.00mm*6.35mm DIP Type	
SIZE	DRAWING No.
A4	YL-ED-XXX
SCALE	SHEET
1 : 1	1 of 1